
VERTICAL FUSE ENTRY




Low Profile




.016 (.41) thick Brass, Tin Plate Current Rating: 30 Amps @ 500V AC



Pad Layout For Two Clips



AVAILABLE ON TAPE AND REEL



Surface Mount



Low Profile

CAT. NO. 3563 (Bulk)

CAT. NO. 3563TR (Tape & Reel)

Tape & Reel Spec's: 24mm wide; 12mm pitch; 13 inch reel (1500 pieces per reel)



CAT. NO. 3564


SPECIFICATIONS


Ō

Material: .012 (.30) thick Brass, Tin Nickel Plate Insulator: Glass filled Nylon, UL Rated 94V-0 Current Rating: 30 Amps @ 500V AC


.120 [3.1] DIA (2) PLS

Temperature Rating: -58°F to+292°F (-50°C to+145°C)





00 .065 [1.65] DIA. (4) PLS





CAT. NO. 3544-2



"AUTO" FUSE CLIPS & HOLDERS

LOW PROFILE MINI FUSE HOLDER

For Littelfuse Low Profile Mini 897 series or equivalent

780 [19.8]

.530 [13.5]

- · Low insertion force
- Thru hole PC mountable, maintains position during wave soldering
- · Fuse holder fully insulates clips to protect fuse from shorting
- Holder assures proper spacing and reduces assembly time

ە ڧ

SPECIFICATIONS

Contacts: .016 (.41) thick Brass, Tin Nickel Plate

Insulator: PBT, UL Rated 94V-0 Current Rating: 20 Amps @ 500V AC Temperature Rating: -58°F to+292°F (-50°C to+145°C)




Mounting Detail [9.74] Ó 0 [3.40]

Q

.067 [1.70] DIA. (4) PLS

MINI FUSE HOLDER

For Littelfuse Mini 297 or 997 series/Bussmann ATM or equivalents





CAT. NO. 3568



Clip details HORIZONTAL FUSE ENTRY

For Littelfuse Mini 297 or 997 series/Bussmann ATM series or equivalent

SPECIFICATIONS

Mounting Detail

Ó .134 [3.4]

0

.530 [13.5]

2.067 [1.70] DIA. (4) PLS


Ó

Contacts: .012 (.30) thick Brass, Tin Nickel Plate

Insulator: PBT, UL Rated 94V-0


Current Rating: 30 Amps @ 500V AC
Temperature Rating: -58°F to+292°F (-50°C to+145°C)





CAT. NO. 3549





CAT. NO. 3549-2

