

REEL DIA.
SEE NOTE #2

FEED DIRECTION

.500 [12.7] MIN.
DIA.HOLE THRU

$\pm .005$ [± 0.13]
1.260 [32.00]

$\pm .005$ [± 0.13]
.157 [4.00]

$\pm .005$ [± 0.13]
 $\emptyset .059$ [1.50]
HOLE (TYP.)

.069 [1.75]

.787 [20.0]

.413 [10.5]
REF.

$\pm .005$ [± 0.13]
1.732 [44.00]

FEED DIRECTION

.016 [0.4]
REF.

KEYSTONE ELECTRONICS CORP. AND
SHALL NOT BE REPRODUCED, DISTRIBUTED,
OR USED AS A BASIS FOR MANUFACTURE
WITHOUT PRIOR WRITTEN PERMISSION
FROM KEYSTONE ELECTRONICS CORP.

1. TAPE:
MAT'L - ALL CONDUCTIVE POLYSTYRENE CARRIER
ANSI/EIA-481 STANDARD
2. REEL:
13.0 [330.2] DIA. 200 PIECES OF
1.732 [44.0] WIDE; 1.260 [32.0] PITCH
3. MSL PACKAGING 1 REEL PER BAG

9.18.23 ADDED PACKAGING INFORMATION CHANGE AS PER ECN 23-164 A			KEYSTONE ELECTRONICS CORP. www.keyelco.com • NEW HYDE PARK NY 11040 • Tel (516)328-7500			
			PART NAME 20mm SM COIN CELL HOLDER ON TAPE&REEL			
			MATERIAL AS NOTED			
			FINISH AS NOTED		DRN BY NT	DATE 3.19.09
					APP'D RH	SCALE X
DATE	DESCRIPTION	REV.	TOLERANCES INCH [MM] DECIMAL ± .015 [± 0.38] ANGULAR ± 1° UNLESS OTHERWISE SPECIFIED	CODE C	DWG NO. 1081TR	