



- NOTE:
1. BASE: MAT'L: HEAT RESISTANCE NYLON STANYL 46 OR EQUIVALENT
 2. POSITIVE CONTACT: MAT'L: .012 [0.30] THK STAINLESS STEEL FINISH: GOLD PLATE
 3. NEGATIVE CONTACT: BASE MAT'L: .012 [0.30] THK STAINLESS STEEL SORING MAT'L: .020 [0.50] DIA. MUSIC WIRE FINISH: GOLDDPLATE

4. CAN BE USED WITH BATTERIES WITH CIRCUIT PROTECTION: 67mm MAX. LENGTH BATTERY MUST HAVE POSITIVE CONTACT EXTENDED

DATE	DESCRIPTION	REV.
7.11.22	CHANGE AS PER ECN 22-126 TOLERANCE CORRECTED, WAS .005	A

THIS DOCUMENT IS THE PROPERTY OF KEYSTONE ELECTRONICS CORP. AND SHALL NOT BE REPRODUCED, DISTRIBUTED OR USED AS A BASIS FOR MANUFACTURE WITHOUT PRIOR WRITTEN PERMISSION FROM KEYSTONE ELECTRONICS CORP.

KEYSTONE ELECTRONICS CORP. www.keystone.com • NEW HYDE PARK, NY 11040 • Tel (516) 328-7500			
PART NAME			
DUAL SM BATTERY HOLDER, 18650			
MATERIAL			
AS NOTED			
FINISH		AS NOTED	
AS NOTED		DRN BY	NT
AS NOTED		DATE	12.14.18
TOLERANCES		CODE	DWG NO.
INCH	[MM]	C	1134
DECIMAL	± .010 [± 0.25]		
ANGULAR	± 1°	App'D	SCALE
		RH	1.25X