




THIS DOCUMENT IS THE PROPERTY OF
KEYSTONE ELECTRONICS CORP. AND
SHALL NOT BE REPRODUCED, DISTRIBUTED
OR USED AS A BASIS FOR MANUFACTURE
WITHOUT PRIOR WRITTEN PERMISSION
FROM KEYSTONE ELECTRONICS CORP.




ACTUAL SIZE



CONNECTOR SPECIFICATION

1. HOUSING: MAT'L- PA66, UL94V-0
2. POST: MAT'L- COPPER ALLOY
TIN PLATED
3. WAFER: MAT'L- GLASS FILLED PBT, UL94V-0
COLOR- NATURAL



TAPE AND REEL SPECIFICATIONS:

4. TAPE: MAT'L - ALL CONDUCTIVE POLYSTYRENE CARRIER
ANSI/EIA-481 STANDARD
5. REEL: 15.0 [380.8] DIA. 500 PIECES PER REEL
6. KAPTON TAPE TO BE APPLIED TO TOP
SURFACE OF EACH CONNECTOR FOR
VACUUM PICK AND PLACE

KEYSTONE ELECTRONICS CORP.

www.keyelco.com • NEW HYDE PARK, NY 11040 • Tel (516) 328-7500

PART NAME

SM TOP ENTRY CONNECTOR (3 CIRCUITS)

MATERIAL

AS NOTED

FINISH

AS NOTED

DRN BY

NT

DATE

10.07.21

APP'D

RH

SCALE

4X

TOLERANCES

INCH

[MM]

DECIMAL

± .005 [± 0.13]

ANGULAR

± 1°

UNLESS OTHERWISE SPECIFIED

CODE

DWG NO.

C

964

DATE

DESCRIPTION

REV.