

THIS DOCUMENT IS THE PROPERTY OF
KEYSTONE ELECTRONICS CORP. AND
SHALL NOT BE REPRODUCED, DISTRIBUTED
OR USED AS A BASIS FOR MANUFACTURE
WITHOUT PRIOR WRITTEN PERMISSION
FROM KEYSTONE ELECTRONICS CORP.



M3 x 0.5 THREAD STANDOFF ENGINEERING KIT				
HEX. =	Threaded Female		Threaded Male/Female	
.200 [5.00]	Brass	Nylon	Brass	Nylon
Length	Cat. No.	Cat. No.	Cat. No.	Cat. No.
.400 [10.0]	24393	25510	24313	25501
.472 [12.00]	24394	25511	24314	25502
.600 [15.00]	34395	25512	24315	25503
.800 [20.00]	24397	25514	24317	25505
Cat. No. 29311 M3 x 6 mm Slot Drive Machine Screw				



NOTES:

1. A KIT HAS 25 PIECES OF EACH CAT.NO. FOR A TOTAL QUANTITY OF 425 PIECES AND IS HOUSED IN A 16 TRAY, LABELED ENCLOSURE.
2. MAT'L - BRASS, NICKEL PLATE
MAT'L - NYLON 6/6
3. DRAWS WILL BE ASSEMBLED WITH PLASTIC DIVIDER INSTALLED AND PRODUCT PLACED IN THE FRONT PORTION OF EACH DRAW.
4. SCREWS TO BE PLACED IN THE BACK PORTION OF THE UPPER LEFT MOST DRAW BEHIND MAT'L - STEEL, ZINC PATE

KEYSTONE ELECTRONICS CORP.			
www.keyelco.com • ASTORIA, N.Y. 11105-2017 • Tel (718) 956-8900			
PART NAME			
HEX 5.0mm STANDOFF HARDWARE KITS			
MATERIAL			
AS NOTED			
FINISH		DRN BY	DATE
AS NOTED		NT	4.19.11
		APP'D	SCALE
		LN	-
TOLERANCES	INCH	[MM]	CODE
DECIMAL	±	[±]	C/M
ANGULAR	±		
UNLESS OTHERWISE SPECIFIED			
		DWG NO.	
			STR-M3

DATE	DESCRIPTION	REV.