



NOTE:

1. BASE:
MAT'L: HEAT RESISTANCE NYLON
STANLYL 46 OR EQUIVALENT
2. CONTACT:
MAT'L: .012 [0.30] THK STAINLESS STEEL
FINISH: GOLD FLASH, OVER NICKEL PLATE
3. BATTERY HOLDER SUPPLIED IN MSL-2 PACKAGING
200 PIECES OF P/N 1042 PER BAG
4. CAN BE USED WITH BATTERIES WITH
CIRCUIT PROTECTION: 67mm MAX. LENGTH

DATE	DESCRIPTION	REV.
10.24.10	AS PER ECN 10-062	A
10.04.10	CHANGE AS PER ECN 10-069	B
10.26.10	CHANGE AS PER ECN 10-075	C
4.12.11	CHANGE AS PER ECN 11-049	D
1.08.18	CHANGE AS PER ECN 18-002 E1 WAS 3.386 [86.00] ADJUST MOUNTING LAYOUT TO MAX. TOLERANCE. CONTACT MAT'L WAS PHOSPHOR BRONZE	E
2.09.23	CHANGE AS PER ECN 23-017 ADDED NOTE #3	F
5.31.23	CHANGE AS PER ECN 23-087 G1 WAS 3.034±.010	G

KEYSTONE ELECTRONICS CORP.

www.keystone.com • NEW HYDE PARK, NY 11040 • Tel (516) 328-7500

PART NAME: PC BATTERY HOLDER, 18650
MATERIAL: AS NOTED

FINISH: AS NOTED
TOLERANCES: INCH [MM]
DECIMAL ± .010 [± 0.25]
ANGULAR ± 1°
CODE: C
DWG NO.: 1042

THIS DOCUMENT IS THE PROPERTY OF
KEYSTONE ELECTRONICS CORP. AND
SHALL NOT BE REPRODUCED, DISTRIBUTED
OR USED AS A BASIS FOR MANUFACTURE
WITHOUT PRIOR WRITTEN PERMISSION
FROM KEYSTONE ELECTRONICS CORP.